



बी.पी. कोइराला स्वास्थ्य बिज्ञान प्रतिष्ठान, धरानको

कोटेशन माग गरिएको सुचना

सुचना प्रकाशित मिति २०८०/११/२४

यस प्रतिष्ठानलाई आवश्यक तपशिलका उल्लेखित Computer/ Laptop/ Printer Goods खरिद गर्नु पर्ने भएकोले इजाजत प्राप्त प्रतिष्ठानमा सुचिकृत फर्म, संस्था, कम्पनीबाट अद्यावधिक फर्म दर्ता प्रमाणपत्र, मु.अ.कर दर्ता प्रमाणपत्र, आ.व. २०७९/०८० को कर चुक्ताको प्रमाणपत्र प्रतिहरु संलग्न गरी यो सुचना प्रकाशित मितिले ७ दिन भित्र कोटेशन पेश गर्नुहुन सुचित गरिन्छ। माग गरिएको कोटेशन तोकिएको म्यादभित्र प्रतिष्ठानको दर्ता चलानी फांटमा खामबन्दि दर्ता गर्नुहुन वा quotation.procurement@bpkihs.edu मा email मार्फत पेश गर्नुपर्नेछ।

SN.	Particular	Qty.	Unit	Description
1	Branded Computer Set	30	Set	Branded
2	UPS 1 Kva	50	Nos	ISI/ ISO Certified
3	Laser Printer (Prefer Canon 2900)	50	Nos	ISI/ ISO Certified
4	Laser Printer for Bill Counter	15	Nos	ISI/ ISO Certified
5	Heavy Duty Laser Printer for CLS Reporting Counter	3	Nos	ISI/ ISO Certified
6	Heavy Duty Scanner (Prefer Canon)	7	Nos	ISI/ ISO Certified
7	Label Sticker Printer	10	Nos	ISI/ ISO Certified
8	Barcode Scanner	25	Nos	ISI/ ISO Certified

Item Name	Specification
Laser Printer	
Printing Speed	12ppm (A4)
Resolution	Enhanced : True 600 x 600dpi resolution Smoothing Technology : (2400 x 600dpi equivalent wjth Automatic Image Refinement Technology)
Printing Language	CAPT (Canon Advanced Printing Technology)
Memory	Uses PC memory (standard 2MB on-board)
First Print Out Time	Front Tray : A4, B5, A5, LGL*, LTR, Executive, Envelope C5 / COM10 / DL, Monarch * LGL refers to paper measuring 215.9 x 355.6mm (8.5 x14 inches) Manual Tray : Custom paper (Width: 76.2 - 215.9mm; Length: 127.0 - 355.6mm)
Paper Input	Front Tray: 150 sheets Manual Tray : 1 sheet Face Down : 100 Sheets
Dimensions (W x D x H)	370 x 251 x 217mm
Weight	Approx. 5.7kg excluding cartridge
Operating Systems Supported	Windows 98 / ME / 2000 / XP, Linux (CUPS)
Power Requirement	220 – 240V (+/-10%), 50 / 60Hz (+/-2Hz)
Interface	USB 2.0 Hi-Speed
Toner Cartridge	Canon Cartridge 303 Power up your LBP2900 and reduce overall print costs by using original Canon cartridges. Designed with advanced Canon technologies, a single Canon Cartridge 303 prints 2000 A4 pages with 5% coverage

Item Name	Specification
Branded Computer	INTEL CORE I7 11TH GENERATION, SSD 1 TB OR HIGHER, RAM 8 GB or Higher, Monitor 18 Inch, Keyboard, Mouse
UPS	1 KVA
Laser Printer	Canon LBP 2900
Heavy Duty Laser Printer	Monochrome Laser Beam Printing, Simplex: A4: up to 40 ppm (pages per minute) A3: up to 20 ppm (pages per minute) Duplex: A4: up to 40 ppm (pages per minute), 600 x 600 dpi equivalent (1200 Equivalent x 1200 dpi quality with Image Refinement Technology), From Power On: 29 sec or less From Quick Start: 17 sec or less, First Print Out Time Approx. 9.3 sec UFR II, PCL5e/6, PostScript 3, PDF, XPS Standard Fonts PCL: 93 fonts PS/PDF: 136 fonts Available Paper Size for Auto Duplex Print A3, B4, A4, A4R, B5, A5, Ledger, LTR, LTR-R, Legal2, Exe Print Margins 5mm-top, bottom, left and right (Envelope: 10mm) Direct Print TIFF, JPEG, PDF, XPS (via USB Host 2.0) Paper Sizes Standard: A3, B4, A4, A4R, B5, A5, Ledger, LTR-R, Legal2, Exe, foolscap, 8K, 16K, Custom Size available3 Multi-Purpose Tray: A3, B4, A4, A4R, B5, A5, Ledger, LTR, LTR-R, Legal2, Exe, STMT, foolscap, 8K, 16K, Custom Media: 210.0 - 297.0mm x 470.1 - 1200mm (only with UFR II printer driver) Optional Paper Feeder PF-A1: A3, B4, A4, A4R, B5, A5, Ledger, LTR, LTR-R, Legal2, Exe, STMT, foolscap, 8K, 16K, Custom Size available3

Label Sticker Printer	Label printer Roll (4.52 in) up to 360 inch/min LAN black direct thermal / thermal transfer 203 dpi USB serial
Barcode Scanner	450 scans per second and working range from contact to 600mm on medium density barcodes. AS-8312 Support PDF417 decoding. General Purpose reader, — a single device covering the broadest range of application. Durable — without any moving parts to wear out. Plug and play connectivity — All popular interfaces are on board KBW / USB / RS-232. Aiming line- Aiming line for easy-of-use in scanning barcode. Excellent Scanning Performance starting at 0.1mm (4 mil). Readable Under Sun Light. Support GS1 databar (RSS); CS (Composite Symbology) barcodes. Reliability (1) Trigger: 1,000,000 times. (2) Cable: 320,000 times (90°). (3) Drop: 1.5 meter.
Heavy Duty Scanner	Document feeding : Flatbed and ADF Light Source : LED Output Resolution (dpi) : 1200 X 1200 Grayscale mode : 16-bit input 8-bit output Color mode : 48-bit input 24-bit output Memory Size : 64 MB SDRAM Interface : USB 2.0 (USB 3.0 compatible) Daily Volum: up to 3000 Sheets ADF Capacity : 50 Sheets